



221 Corporate Circle, Unit H
Golden, CO 80401
Tel: 303-237-9608
Fax: 303-237-0757
www.carsaneng.com

ISO 9001:2000
ISO 13485:2003
REGISTERED

CE180AXE and CE180BXE **Xenon Power Supply Specification**

The CE180 power supply is designed to run xenon arc lamps in a constant-current mode. The supply is designed to operate 175-watt xenon arc-lamps. The output current is adjustable from 10 to 15 Amps via a potentiometer on the circuit board. EMI line-filtering is built-in to the unit. The CE180BXE is the same as the A-model except it does not have Y-capacitors in the line filter section.

Output power: 110 - 224 Watts, constant current

Output voltage compliance: 11.0 to 17.0 V operating, >110 VDC during ignition.

Output regulation: output current held to within +/- 5% over all input, output, and environmental conditions.



Output current: 10.0 to 15.0 Adc

Output ripple: <0.7 Ap-p*

Efficiency: >72% at 200 W output, 120 VAC input

Thermal protection: ballast is disabled when temperature exceeds 90 deg C.

Unit will automatically restart after cooling down.

Auxiliary output (non-isolated): +12V fan power, 650 mA max.
12.0V to 12.8V at 250mA load.

Optically Isolated Status & Control Connector (UL-rated circuit)

- Remote Enable
- Lamp Lit Status
- Remote Lamp Intensity Control

Ground Leakage:

AXE: <300 μ A at 136 VAC, <500 μ A at 265 VAC

BXE: <10 μ A at all input voltages

Regulatory Compliance:

Approved to UL2601 (E177225). Complies with EN55011 Class B Emissions.
CE-marked.



Line Input: 100 - 240 VAC, +/- 10%, 47 - 63 Hz, 4.6 Arms max.

Input Surge Current: <30 Amps peak at turn-on, for all input voltages.

Environmental: 0 deg C to 45 deg C operating.

Altitude: -1000 ft. to 12,000 ft. MSL.

Weight: 2.5 lbs (1.14 Kg).

Dimensions: 6.00" x 4.15", 2.80" tall (152mm x 105mm, 71mm tall).

Ignitor:

25 - 30 KV ignition spike. Negative-side ignition.

Minimum repetition rate is 0.8 strikes/second at 90 VAC. Typical repetition rate is 1.2 strikes/second (120 VAC). Ignition pulses will continue until lamp ignites.

* ripple is measured in a DC to 20 MHz bandwidth.

Specifications subject to change without notice.